

NRB 0800-2406 Q

Air-water chiller with shell and tube heat exchanger

Cooling capacity 216,9 ÷ 716,9 kW



- **Microchannel coil**
- **Shell and tube heat exchanger**
- **Night mode**
- **Operation up to 50 °C outdoor air**
- **HP floating: ESEER +7% with inverter fans**



DESCRIPTION

Air-cooled outdoor chiller designed to meet air conditioning needs in residential/commercial complexes or industrial applications.

They are outdoor units with axial fan scroll compressors, microchannel coils and Shell and tube exchangers.

In the unit with desuperheater, it is also possible to produce free-hot water. The base, the structure and the panels are made of galvanized steel treated with polyester paint RAL 9003.

VERSIONS

- ° Standard
- A High efficiency
- E Silenced high efficiency
- L Standard silenced
- N Silenced very high efficiency
- U Very high efficiency

FEATURES

Operating field

Operation at full load up to 50°C external air temperature. Unit can produce chilled water (up to -10°C of water produced in some versions).

Dual-circuit unit

Unit with 2 refrigerant circuits designed to provide maximum efficiency at full load, ensuring high efficiency at partial loads also and ensuring continuity in case one of the circuits stops.

Aluminium microchannel coils

The microchannel condensing aluminum coils ensure high levels of efficiency, reduced quantities of refrigerant and lower unit weight. The treatment "O" available as configurator it ensures high resistance to corrosion even in the most aggressive environments.

Electronic expansion valve

The possibility to use electronic expansion valve, offers significant benefits, especially when the chiller is working with partial loads, increasing the energy efficiency of the unit.

It is standard in all sizes from 1805 to 2406.

Option integrated hydronic kit

Integrated hydronic kit containing the main hydraulic components; available with various configurations with one or two pumps, high or low head, to obtain a solution that allows you to save money and to facilitate installation.

CONTROL PCO⁵

Microprocessor adjustment, with 7", touch screen keyboard, which allows to navigate intuitively among the various screens, allowing to modify the operating parameters and graphically view the progress of some variables in real time and the ad adjustment includes complete management of the alarms and their log.

- Possibility to control two units in a Master-Slave configuration
- The presence of a programmable timer allows functioning time periods and a possible second set-point to be set.
- The temperature control takes place with the integral proportional logic, based on the water output temperature.
- **Floating HP control:** available for all models with inverter fans or with DCPX. Together with continuous fan modulation, it optimises unit operation in any working point, enhancing energy efficiency with partial loads. **ESEER up to +7% with inverter fans.**
- **Night mode:** only in the **non-silenced versions with the fan to be, inverter or phase-cut or with the DCPX accessory**, a silenced operation profile can be set, which is useful, for example, at night for greater acoustic comfort, but always ensures performance even at peak load hours.

CONFIGURATOR

Field	Description
1,2,3	NRB
4,5,6,7	Size 0800, 0900, 1000, 1100, 1200, 1400, 1600, 1805, 2006, 2206, 2406
8	Operating field
X	Electronic thermostatic expansion valve (1)
Y	Low temperature mechanic thermostatic valve (2)
Z	Low temperature electronic thermostatic valve (2)
°	Standard mechanic thermostatic valve (1)
9	Model
Q	Cooling only with shell and tube heat exchanger
10	Heat recovery
D	With desuperheater (3)
T	With total recovery (4)
°	Without heat recovery
11	Version
°	Standard
A	High efficiency
E	Silenced high efficiency
L	Standard silenced
N	Silenced very high efficiency
U	Very high efficiency
12	Coils
I	Copper-aluminium
O	Coated aluminium microchannel
R	Copper pipes-copper fins
S	Copper pipes-Tinned copper fins
V	Copper pipes-Coated aluminium fins
°	Aluminium microchannel
13	Fans
J	Inverter
M	Oversized

Compatible with total recovery

Version		800	900	1000	1100	1200	1400	1600	1805	2006	2206	2406
standard	°	-	-	-	-	-	-	-	-	-	-	•
Standard silenced	L	-	-	-	-	-	-	-	-	•	•	•
High efficiency	A	-	-	-	-	-	-	-	-	•	•	•
Silenced high efficiency	E	-	-	-	-	-	-	•	•	•	•	•
Very high efficiency	U	-	-	-	-	-	-	•	•	•	•	•
Silenced very high efficiency	N	-	-	-	•	•	•	•	•	•	•	•

Compatibility of models with hydronic units available with a configurator

Version		0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406
standard	°	-	-	-	-	•	-	-	•	•	•	•
Standard silenced	L	-	-	•	-	-	-	•	•	•	•	•
High efficiency	A	-	-	•	-	-	-	•	•	•	•	•
Silenced high efficiency	E	•	•	-	•	•	•	•	•	•	•	•
Very high efficiency	U	•	•	-	•	•	•	•	•	•	•	•
Silenced very high efficiency	N	•	•	•	•	•	•	•	•	•	•	•

ACCESSORIES

AER485P1: RS-485 interface for supervising systems with MODBUS protocol. 1 accessory is provided for each unit control board.

AERBACP: Ethernet communication interface for Bacnet/IP, Modbus TCP/IP, SNMP protocols. 1 accessory is provided for each unit control board.

AERLINK: Aerlink is a WiFi gateway with an RS485 serial port that allows a wide range of Aermec products (heat pumps/chillers/system controllers) equipped with this interface to connect easily and securely to a Wi-Fi network. It works both as an access point (AP access point) and as a client (WiFi Station), it can be connected to a single generator or system centraliser, allowing anyone to easily integrate them into any network. Thanks to the AerApp and AerPlants apps, which can be used on Android and iOS platforms, the remote management of the air conditioning systems developed by Aermec becomes intuitive and simple.

AERNET: The device allows the control, the management and the remote monitoring of a Chiller with a PC, smartphone or tablet using Cloud connection. AERNET works as Master while every unit connected is configured as Slave (max. 6 control boards). Also, with a simple click is possible to save a log file with all the connected unit datas in the personal terminal for post analysis.

FL: Flow switch.

Field	Description
14	Power supply
°	400V ~ 3 50Hz with magnet circuit breakers
15,16	Integrated hydronic kit
	Without hydronic kit (5)
00	Without hydronic kit
	Kit with n° 1 pump
PA	Pump A
PB	Pump B
PC	Pump C
PD	Pump D
PE	Pump E
PF	Pump F
PG	Pump G
PH	Pump H
PI	Pump I
PJ	Pump J
	Pump n° 1 pump + stand-by pump
DA	Pump A + stand-by pump
DB	Pump B + stand-by pump
DC	Pump C + stand-by pump
DD	Pump D + stand-by pump
DE	Pump E + stand-by pump
DF	Pump F + stand-by pump
DG	Pump G + stand-by pump
DH	Pump H + stand-by pump
DI	Pump I + stand-by pump
DJ	Pump J + stand-by pump

(1) Water produced from 4 °C ÷ 18 °C

(2) Processed water from 4°C to -8°C for the ° - L versions, and from 4°C to -10°C for A - E - U - N versions

(3) The temperature of the water in the heat exchanger inlet must never drop below 35°C.

(4) For compatibility with total recovery see table below.

(5) For compatibility with the hydronic kit, see the table below.

MULTICHILLER-EVO: Control, switch-on and switch-off system of the single chillers where multiple units are installed in parallel (max. no. 9), always ensuring constant flow rate to the evaporators.

PGD1: Allows you to control the unit at a distance.

PR4: Remote panel with LCD display and touch keyboard that allows carrying out the basic controls, the programming of time ranges and the signalling of the alarms of a single unit.

■ *The accessory PR4 should only be combined with the RS485 communication interface when the serial port is occupied by another device.*

AVX: Spring anti-vibration supports.

DCPX: Device for condensation temperature control, with continuous speed modulation of fans by using a pressure transducer.

FACTORY FITTED ACCESSORIES

DRE: Electronic device for peak current reduction.

RIF: Power factor correction. Connected in parallel to the motor allowing about 10% reduction of input current.

GP_: Anti-intrusion grid kit

KRS: Electric heater for the heat exchanger

ACCESSORIES COMPATIBILITY

Model	Ver	0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406
AER485P1	°A,E,L,N,U
AERBACP	°A,E,L,N,U
AERNET	°A,E,L,N,U
FL	°A,E,L,N,U
MULTICHILLER-EVO	°A,E,L,N,U
PGD1	°A,E,L,N,U

Remote panel

Model	Ver	0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406
PR4	°A,E,L,N,U

The accessory PR4 should only be combined with the RS485 communication interface when the serial port is occupied by another device.

Condensation control temperature

Ver	0800	0900	1000	1100	1200	1400
Fans: M						
°	DCPX130	DCPX130	DCPX130	DCPX130	DCPX130	DCPX131
A	DCPX130	DCPX130	DCPX131	DCPX131	DCPX131	DCPX131
E, L, N	As standard	As standard	As standard	As standard	As standard	As standard
U	DCPX131	DCPX131	DCPX131	DCPX132	DCPX132	DCPX132
Ver	1600	1805	2006	2206	2406	
Fans: M						
°	DCPX131	DCPX155	DCPX155	DCPX155	DCPX156	
A	DCPX132	DCPX155	DCPX156	DCPX156	DCPX134	
E, L, N	As standard	As standard	As standard	As standard	As standard	
U	DCPX133	DCPX134	DCPX134	DCPX135	DCPX135	

Antivibration

Ver	0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406
Integrated hydronic kit: 00											
°	AVX1107	AVX1107	AVX1107	AVX1107	AVX1108	AVX1108	AVX1108	AVX1109	AVX1109	AVX1109	AVX1110
A, L	AVX1107	AVX1107	AVX1108	AVX1108	AVX1108	AVX1108	AVX1109	AVX1109	AVX1110	AVX1110	AVX1111
E, U	AVX1108	AVX1108	AVX1108	AVX1109	AVX1109	AVX1109	AVX1110	AVX1111	AVX1111	AVX1105	AVX1105
N	AVX1109	AVX1109	AVX1109	AVX1110	AVX1110	AVX1110	AVX1111	AVX1105	AVX1105	AVX1102	AVX1102
Integrated hydronic kit: DA, DB, DC, DD, DE, DF, DG, DH, DI, DJ, PA, PB, PC, PD, PE, PF, PG, PH, PI, PJ											
°	-	-	-	-	AVX1108	-	-	AVX1109	AVX1109	AVX1109	AVX1110
A, L	-	-	AVX1108	-	-	-	AVX1109	AVX1109	AVX1110	AVX1110	AVX1111
E, U	AVX1108	AVX1108	-	AVX1109	AVX1109	AVX1109	AVX1110	AVX1111	AVX1111	AVX1105	AVX1105
N	AVX1109	AVX1109	AVX1109	AVX1110	AVX1110	AVX1110	AVX1111	AVX1105	AVX1105	AVX1102	AVX1102

Device for peak current reduction

Ver	0800	0900	1000	1100	1200	1400
°A, E, L, N, U	DRENRB0800 (1)	DRENRB0900 (1)	DRENRB1000 (1)	DRENRB1100 (1)	DRENRB1200 (1)	DRENRB1400 (1)

(1) Only for supplies of 400V 3N ~ 50Hz and 400V 3 ~ 50Hz. x 2 or x 3 (if present) indicates the quantity to be ordered.
A grey background indicates the accessory must be assembled in the factory

Ver	1600	1805	2006	2206	2406
°A, E, L, N, U	DRENRB1600 (1)	DRENRB1805 (1)	DRENRB2006 (1)	DRENRB2206 (1)	DRENRB2406 (1)

(1) Only for supplies of 400V 3N ~ 50Hz and 400V 3 ~ 50Hz. x 2 or x 3 (if present) indicates the quantity to be ordered.
A grey background indicates the accessory must be assembled in the factory

Power factor correction

Ver	0800	0900	1000	1100	1200	1400
°A, L	RIFNRB0800	RIFNRB0900	RIFNRB1000	RIFNRB1100	RIFNRB1200	RIFNRB1400
E, U	RIFNRB0800	RIFNRB0900	RIFNRB1000	RIFNRB1101	RIFNRB1201	RIFNRB1401
N	RIFNRB0801	RIFNRB0901	RIFNRB1001	RIFNRB1101	RIFNRB1201	RIFNRB1401

A grey background indicates the accessory must be assembled in the factory

Ver	1600	1805	2006	2206	2406
°	RIFNRB1600	RIFNRB1805	RIFNRB2006	RIFNRB2206	RIFNRB2406
A, L	RIFNRB1601	RIFNRB1805	RIFNRB2006	RIFNRB2206	RIFNRB2416
E, N, U	RIFNRB1601	RIFNRB1815	RIFNRB2016	RIFNRB2216	RIFNRB2416

A grey background indicates the accessory must be assembled in the factory

Anti-intrusion grid

Ver	0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406
Integrated hydronic kit: 00											
°	GP2VN	GP2VN	GP2VN	GP2VN	GP3VN	GP3VN	GP3VN	GP4VN	GP4VN	GP4VN	GP5VN
A, L	GP2VN	GP2VN	GP3VN	GP3VN	GP3VN	GP3VN	GP4VN	GP4VN	GP5VN	GP5VN	GP5VN
E, U	GP3VN	GP3VN	GP3VN	GP4VN	GP4VN	GP4VN	GP5VN	GP6V	GP6V	GP7V	GP7V
N	GP4VN	GP4VN	GP4VN	GP5VN	GP5VN	GP5VN	GP6V	GP7V	GP7V	GP8V	GP4VN
Integrated hydronic kit: DA, DB, DC, DD, DE, DF, DG, DH, DI, DJ, PA, PB, PC, PD, PE, PF, PG, PH, PI, PJ											
°	-	-	-	-	GP3VN	-	-	GP4VN	GP4VN	GP4VN	GP5VN
A, L	-	-	GP3VN	-	-	-	GP4VN	GP4VN	GP5VN	GP5VN	GP5VN
E, U	GP3VN	GP3VN	-	GP4VN	GP4VN	GP4VN	GP5VN	GP6V	GP6V	GP7V	GP7V
N	GP4VN	GP4VN	GP4VN	GP5VN	GP5VN	GP5VN	GP6V	GP7V	GP7V	GP8V	GP4VN

A grey background indicates the accessory must be assembled in the factory

Kit for low temperature

Ver	0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406
°	-	-	-	-	-	-	-	XLA (1)	XLA (1)	XLA (1)	XLA (1)
A, L	-	-	-	-	-	-	XLA (1)	XLA (1)	XLA (1)	XLA (1)	XLA (1)
E, U	-	-	-	XLA (1)	XLA (1)	XLA (1)	XLA (1)	XLA (1)	XLA (1)	XLA (1)	XLA (1)
N	XLA (1)	XLA (1)	XLA (1)	XLA (1)	XLA (1)	XLA (1)	XLA (1)	XLA (1)	XLA (1)	XLA (1)	XLA (1)

(1) With the accessory XLA do not use the DCPX.

The accessory cannot be fitted on the configurations indicated with -

A grey background indicates the accessory must be assembled in the factory

PERFORMANCE SPECIFICATIONS

NRB - °

Size		0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406
Cooling performance 12 °C / 7 °C (1)												
Cooling capacity	kW	221,5	244,5	270,3	299,7	353,1	404,9	439,0	511,2	560,9	598,2	675,8
Input power	kW	73,3	83,1	94,1	110,3	117,5	135,4	155,1	175,7	194,0	216,6	236,5
Cooling total input current	A	128,3	143,1	160,0	185,5	201,6	229,9	260,8	299,7	329,8	366,5	404,6
EER	W/W	3,02	2,94	2,87	2,72	3,00	2,99	2,83	2,91	2,89	2,76	2,86
Water flow rate system side	l/h	38117	42077	46498	51565	60733	69640	75512	87913	96469	102883	116222
Pressure drop system side	kPa	46	55	38	45	44	39	46	40	47	53	52

(1) Data EN 14511:2022; Heat exchanger water (services side) 12°C / 7°C; outside air 35°C

NRB - L

Size		0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406
Cooling performance 12 °C / 7 °C (1)												
Cooling capacity	kW	216,9	237,7	272,7	307,7	343,9	391,0	438,4	498,2	555,4	608,2	666,2
Input power	kW	73,0	85,9	92,0	107,4	122,7	139,0	151,9	173,3	191,6	213,6	233,8
Cooling total input current	A	122,8	142,3	154,5	179,0	203,4	231,8	250,8	289,7	318,6	359,2	390,2
EER	W/W	2,97	2,77	2,97	2,87	2,80	2,81	2,89	2,87	2,90	2,85	2,85
Water flow rate system side	l/h	37323	40891	46905	52926	59137	67243	75381	85669	95498	104586	114564
Pressure drop system side	kPa	25	20	27	24	29	23	30	28	37	36	44

(1) Data EN 14511:2022; Heat exchanger water (services side) 12°C / 7°C; outside air 35°C

NRB - A

Size		0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406
Cooling performance 12 °C / 7 °C (1)												
Cooling capacity	kW	224,1	252,2	283,7	326,1	361,2	411,7	462,2	519,2	576,0	633,3	697,6
Input power	kW	70,6	80,9	90,2	104,7	115,3	131,8	147,6	166,3	183,5	203,1	223,3
Cooling total input current	A	123,9	139,9	158,8	181,8	198,2	224,1	252,4	283,8	316,2	348,7	386,3
EER	W/W	3,17	3,12	3,15	3,12	3,13	3,12	3,13	3,12	3,14	3,12	3,12
Water flow rate system side	l/h	38561	43394	48802	56076	62118	70789	79487	89271	99048	108894	119965
Pressure drop system side	kPa	27	22	30	27	32	25	34	30	39	39	48

(1) Data EN 14511:2022; Heat exchanger water (services side) 12°C / 7°C; outside air 35°C

NRB - E

Size		0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406
Cooling performance 12 °C / 7 °C (1)												
Cooling capacity	kW	219,2	248,3	275,0	321,4	358,7	403,2	455,0	514,5	569,0	637,2	688,3
Input power	kW	69,6	79,4	88,5	102,2	114,9	129,8	144,5	164,7	183,0	203,4	221,4
Cooling total input current	A	119,5	134,7	148,8	172,1	192,6	215,7	240,1	275,1	306,1	342,6	372,8
EER	W/W	3,15	3,13	3,11	3,15	3,12	3,11	3,15	3,12	3,11	3,13	3,11
Water flow rate system side	l/h	37710	42726	47303	55271	61679	69338	78240	88465	97841	109550	118323
Pressure drop system side	kPa	19	23	20	27	21	27	26	33	33	22	25

(1) Data EN 14511:2022; Heat exchanger water (services side) 12°C / 7°C; outside air 35°C

NRB - U

Size		0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406
Cooling performance 12 °C / 7 °C (1)												
Cooling capacity	kW	227,6	257,6	286,5	329,6	369,8	414,6	466,9	529,2	594,0	655,1	716,9
Input power	kW	68,8	77,7	86,8	99,5	111,7	126,1	140,9	159,5	179,0	197,8	215,3
Cooling total input current	A	124,3	138,5	152,9	176,0	195,6	218,0	244,0	278,3	311,7	347,7	377,4
EER	W/W	3,30	3,31	3,30	3,31	3,31	3,28	3,31	3,32	3,32	3,31	3,33
Water flow rate system side	l/h	39151	44308	49294	56689	63596	71302	80286	91003	102137	112618	123250
Pressure drop system side	kPa	20	25	21	29	23	28	27	35	36	23	27

(1) Data EN 14511:2022; Heat exchanger water (services side) 12°C / 7°C; outside air 35°C

NRB - N

Size		0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406
Cooling performance 12 °C / 7 °C (1)												
Cooling capacity	kW	227,7	260,4	284,7	327,7	367,7	412,3	466,1	521,6	579,1	645,7	702,6
Input power	kW	68,5	78,9	86,4	98,5	111,9	125,4	140,4	157,8	176,0	194,6	212,9
Cooling total input current	A	118,2	135,1	146,9	166,9	188,6	209,4	234,0	264,2	295,4	328,9	360,0
EER	W/W	3,32	3,30	3,30	3,33	3,29	3,29	3,32	3,31	3,29	3,32	3,30
Water flow rate system side	l/h	39166	44792	48972	56365	63234	70905	80151	89691	99569	111009	120789
Pressure drop system side	kPa	20	25	21	28	23	28	27	34	34	23	26

(1) Data EN 14511:2022; Heat exchanger water (services side) 12°C / 7°C; outside air 35°C

ENERGY INDICES (REG. 2016/2281 EU)

Size		0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406	
Fans: J													
SEER - 12/7 (EN14825: 2018) (1)													
SEER	°	W/W	4,44	4,33	4,27	4,25	4,39	- (2)	- (2)	- (2)	- (2)	- (2)	
	A	W/W	4,65	4,55	4,66	4,70	4,69	4,73	4,76	4,64	4,64	4,62	4,61
	E	W/W	4,75	4,67	4,63	4,81	4,82	4,76	4,88	4,73	4,67	4,70	4,74
	L	W/W	4,56	4,42	4,50	4,51	4,58	4,59	4,67	4,56	4,56	4,58	4,57
	N	W/W	4,85	4,79	4,83	4,96	4,93	4,97	5,03	4,93	4,82	4,89	4,83
	U	W/W	4,76	4,75	4,71	4,89	4,85	4,86	4,91	4,84	4,77	4,82	4,78
Seasonal efficiency	°	%	174,60	170,10	167,60	167,10	172,70	- (2)	- (2)	- (2)	- (2)	- (2)	- (2)
	A	%	182,80	179,10	183,40	185,00	184,70	186,20	187,30	182,70	182,40	181,70	181,50
	E	%	187,00	183,70	182,00	189,30	189,60	187,50	192,30	186,20	183,90	184,80	186,40
	L	%	179,20	173,80	177,00	177,50	180,10	180,40	183,90	179,50	179,40	180,10	179,60
	N	%	191,10	188,40	190,30	195,40	194,20	195,90	198,10	194,10	189,90	192,40	190,00
	U	%	187,40	187,10	185,20	192,50	191,00	191,30	193,30	190,70	187,70	189,60	188,10
SEER - 23/18 (EN14825: 2018) (3)													
SEER	°	W/W	5,28	5,16	5,07	4,96	5,40	5,44	5,18	5,07	5,13	4,77	5,07
	A	W/W	5,50	5,35	5,50	5,51	5,55	5,55	5,63	5,34	5,44	5,30	5,42
	E	W/W	5,62	5,53	5,46	5,70	5,69	5,63	5,77	5,50	5,52	5,48	5,59
	L	W/W	5,34	5,14	5,35	5,33	5,37	5,34	5,47	5,26	5,32	5,20	5,26
	N	W/W	5,92	5,71	5,76	5,91	5,88	5,91	5,99	5,75	5,74	5,71	5,75
	U	W/W	5,65	5,67	5,59	5,82	5,76	5,80	5,83	5,67	5,69	5,61	5,68
Seasonal efficiency	°	%	208,10	203,40	199,80	195,40	212,90	214,50	204,10	199,90	202,10	187,80	199,60
	A	%	217,00	210,90	217,00	217,50	219,10	219,10	222,10	210,50	214,60	209,10	213,60
	E	%	221,90	218,30	215,30	224,90	224,50	222,20	227,70	216,80	217,70	216,00	220,60
	L	%	210,40	202,70	211,00	210,20	211,60	210,40	215,80	207,40	209,70	205,10	207,50
	N	%	229,90	225,30	227,50	233,50	232,10	233,40	236,40	226,80	226,40	225,50	227,10
	U	%	222,80	223,70	220,70	229,90	227,50	228,80	230,20	223,80	224,50	221,50	224,00
SEPR - (EN 14825: 2018) (3)													
SEPR	°	W/W	5,39	5,22	5,17	5,03	5,36	5,51	5,52	5,58	5,52	5,51	5,51
	A	W/W	5,64	5,29	5,58	5,30	5,55	5,52	5,56	5,56	5,57	5,55	5,55
	E	W/W	5,56	5,22	5,47	5,25	5,52	5,56	5,58	5,54	5,53	5,55	5,55
	L	W/W	5,32	5,05	5,31	5,04	5,18	5,05	5,53	5,53	5,53	5,52	5,54
	N	W/W	5,69	5,55	5,67	5,60	5,64	5,62	5,66	5,57	5,67	5,60	5,64
	U	W/W	5,67	5,54	5,66	5,54	5,68	5,59	5,69	5,55	5,55	5,58	5,72

(1) Calculation performed with FIXED water flow rate and VARIABLE outlet temperature.

(2) Non-compliant with 2016/2281 EU regulation for comfort applications 12°C / 7°C

(3) Calculation performed with FIXED water flow rate.

Size			0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406
Fans: M													
SEER - 12/7 (EN14825: 2018) (1)													
SEER	°	W/W	4,23	4,13	4,10	4,11	4,19	- (2)	- (2)	- (2)	- (2)	- (2)	- (2)
	A	W/W	4,41	4,34	4,39	4,45	4,48	- (2)	- (2)	- (2)	- (2)	- (2)	- (2)
	E	W/W	4,47	4,40	4,40	4,54	4,54	- (2)	- (2)	- (2)	- (2)	- (2)	- (2)
	L	W/W	4,31	4,17	4,25	4,27	4,31	- (2)	- (2)	- (2)	- (2)	- (2)	- (2)
	N	W/W	4,61	4,56	4,58	4,72	4,68	4,72	4,78	4,66	4,58	4,61	4,62
	U	W/W	4,51	4,51	4,51	4,63	4,64	4,65	4,70	4,61	4,56	4,57	4,59
Seasonal efficiency	°	%	166,00	162,30	161,00	161,20	164,70	- (2)	- (2)	- (2)	- (2)	- (2)	- (2)
	A	%	173,50	170,60	172,40	174,90	176,00	- (2)	- (2)	- (2)	- (2)	- (2)	- (2)
	E	%	175,60	173,10	173,10	178,70	178,50	- (2)	- (2)	- (2)	- (2)	- (2)	- (2)
	L	%	169,40	163,60	166,80	167,60	169,20	- (2)	- (2)	- (2)	- (2)	- (2)	- (2)
	N	%	181,30	179,30	180,00	185,70	184,10	185,90	188,20	183,40	180,30	181,50	181,60
	U	%	177,20	177,40	177,20	182,10	182,50	183,10	184,80	181,40	179,20	179,90	180,50
SEER - 23/18 (EN14825: 2018) (3)													
SEER	°	W/W	5,08	4,98	4,92	4,82	5,20	5,26	5,03	4,91	4,97	4,63	4,91
	A	W/W	5,29	5,15	5,25	5,28	5,35	5,37	5,42	5,15	5,22	5,09	5,22
	E	W/W	5,36	5,24	5,28	5,40	5,43	5,37	5,54	5,21	5,22	5,21	5,30
	L	W/W	5,06	4,87	5,07	5,08	5,05	5,10	5,19	5,02	5,02	4,92	4,99
	N	W/W	5,57	5,47	5,50	5,66	5,61	5,65	5,73	5,48	5,48	5,44	5,54
	U	W/W	5,41	5,44	5,41	5,58	5,56	5,60	5,63	5,46	5,49	5,39	5,50
Seasonal efficiency	°	%	200,10	196,00	193,60	189,90	205,10	207,30	198,30	193,30	195,70	182,00	193,50
	A	%	208,40	203,00	206,80	208,00	211,10	211,60	213,60	203,10	205,70	200,60	205,60
	E	%	211,40	206,40	208,30	213,00	214,00	211,80	218,50	205,50	205,70	205,30	208,90
	L	%	199,40	191,90	199,70	200,10	199,10	200,80	204,40	197,70	197,60	193,90	196,40
	N	%	219,70	215,80	216,80	223,40	221,50	223,00	226,20	216,00	216,30	214,60	218,40
	U	%	213,40	214,40	213,30	220,00	219,50	221,00	222,20	215,30	216,40	212,50	216,90
SEPR - (EN 14825: 2018) (3)													
SEPR	°	W/W	5,39	5,22	5,17	5,03	5,36	5,51	5,52	5,58	5,52	5,51	5,51
	A	W/W	5,64	5,29	5,58	5,30	5,55	5,52	5,56	5,56	5,57	5,55	5,55
	E	W/W	5,56	5,22	5,47	5,25	5,52	5,56	5,58	5,54	5,53	5,55	5,55
	L	W/W	5,32	5,05	5,31	5,04	5,18	5,05	5,53	5,53	5,53	5,52	5,54
	N	W/W	5,69	5,55	5,67	5,60	5,64	5,62	5,66	5,57	5,63	5,60	5,64
	U	W/W	5,67	5,54	5,66	5,54	5,68	5,59	5,69	5,55	5,55	5,58	5,72

- (1) Calculation performed with FIXED water flow rate and VARIABLE outlet temperature.
(2) Non-compliant with 2016/2281 EU regulation for comfort applications 12°C / 7°C
(3) Calculation performed with FIXED water flow rate.

ELECTRIC DATA

Size			0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406
Electric data													
Maximum current (FLA)	°	A	164,3	180,7	197,0	226,4	262,1	291,1	320,1	371,3	416,0	445,0	480,4
	A,L	A	177,1	193,4	222,5	251,8	281,2	310,2	351,9	396,7	454,2	483,2	530,8
	E,U	A	189,8	206,1	222,5	264,5	293,9	322,9	364,6	428,0	472,8	514,5	543,5
	N	A	202,5	218,8	235,2	277,3	306,6	335,6	383,2	440,7	485,5	527,2	556,2
Peak current (LRA)	°	A	352,9	408,1	424,4	477,1	512,8	625,3	654,3	705,5	750,3	779,3	814,6
	A,L	A	365,6	420,8	449,9	502,5	531,9	644,4	686,1	730,9	788,4	817,4	865,0
	E,U	A	378,3	433,5	449,9	515,3	544,6	657,1	698,8	762,2	807,0	848,7	877,7
	N	A	391,1	446,2	462,6	528,0	557,3	669,8	717,4	774,9	819,7	861,4	890,4

GENERAL TECHNICAL DATA

Size			0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406
Compressor													
Type	°A,E,L,N,U	type	Scroll										
Compressor regulation	°A,E,L,N,U	Type	On/Off										
Number	°A,E,L,N,U	no.	4	4	4	4	4	4	4	5	6	6	6
Circuits	°A,E,L,N,U	no.	2	2	2	2	2	2	2	2	2	2	2
Partialisation of the unit with mechanical thermostatic valve	°A,E,L,N,U	%	25%	25%	25%	25%	25%	25%	25%	17%	17%	17%	17%
Partialisation of the unit with electronic thermostatic expansion valve	°A,E,L,N,U	%	25%	25%	25%	25%	25%	25%	25%	17%	17%	17%	17%
Refrigerant	°A,E,L,N,U	type	R410A										
Refrigerant charge (1)	°	kg	28,0	29,0	30,0	32,0	41,0	42,0	42,0	55,0	55,0	55,0	65,0
	A,L	kg	30,0	32,0	40,0	44,0	42,0	45,0	49,0	55,0	64,0	65,0	70,0
	E,U	kg	41,0	40,0	43,0	53,0	53,0	62,0	69,0	75,0	90,0	90,0	112,0
	N	kg	50,0	53,0	53,0	59,0	59,0	70,0	84,0	80,0	90,0	124,0	91,0
Oil	°A,E,L,N,U	Type											
Oil charge circuit 1	°A,E,L,N,U	kg	9,3	11,5	13,6	13,1	12,6	12,6	12,6	16,6	24,9	24,9	12,6
Oil charge circuit 2	°A,E,L,N,U	kg	9,3	11,5	13,6	13,1	12,6	12,6	12,6	24,9	24,9	24,9	24,9
System side heat exchanger													
Type	°A,E,L,N,U	type	Shell and tube										
Number	°A,E,L,N,U	no.	1	1	1	1	1	1	1	1	1	1	1
Hydraulic connections													
Connections (in/out)	°A,E,L,N,U	Type	Grooved joints										
Hydraulic connections without hydronic kit													
Sizes (in/out)	°	Ø	5"	5"	5"	5"	5"	5"	5"	6"	6"	6"	6"
	A,L	Ø	5"	5"	5"	5"	5"	6"	6"	6"	6"	6"	6"
	E,N,U	Ø	5"	5"	5"	5"	6"	6"	6"	6"	6"	6"	6"
Hydraulic connections with hydronic kit													
Sizes (in/out)	°	Ø	-	-	-	-	3"	-	-	4"	4"	4"	4"
	A,L	Ø	-	-	3"	-	-	-	4"	4"	4"	4"	4"
	E,U	Ø	3"	3"	-	3"	3"	3"	4"	4"	4"	4"	4"
	N	Ø	3"	3"	3"	3"	3"	3"	4"	4"	4"	4"	4"

(1) The load indicated in the table is an estimated and preliminary value. The final value of the refrigerant load is indicated on the unit's technical label. For further information contact the office.

Water filter not supplied. Installation is mandatory or the guarantee will void.


Fans

Size			0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406
Fans: M													
Fan													
Type	°A,E,L,N,U	type	Axial										
Fan motor	°A,U	type	Asynchronous										
	E,L,N	type	Asynchronous with phase cut										
Number	°	no.	4	4	4	4	6	6	6	8	8	8	10
	A,L	no.	4	4	6	6	6	6	8	8	10	10	12
	E,U	no.	6	6	6	8	8	8	10	12	12	14	14
	N	no.	8	8	8	10	10	10	12	14	14	16	16
With static pressure													
Air flow rate	°	m ³ /h	64000	64000	64000	64000	96000	96000	96000	128000	128000	128000	160000
	A	m ³ /h	64000	64000	96000	96000	96000	96000	128000	128000	160000	160000	192000
	E	m ³ /h	69000	69000	69000	92000	92000	92000	115000	138000	138000	161000	161000
	L	m ³ /h	46000	46000	69000	69000	69000	69000	92000	92000	115000	115000	138000
	N	m ³ /h	92000	92000	92000	115000	115000	115000	138000	161000	161000	184000	184000
	U	m ³ /h	96000	96000	96000	128000	128000	128000	160000	192000	192000	224000	224000
High static pressure	°A,U	Pa	50	50	50	50	50	50	50	50	50	50	50
	E,L,N	Pa	120	120	120	120	120	120	120	120	120	120	120
Without Static pressure													
Air flow rate	°	m ³ /h	72000	72000	72000	72000	108000	108000	108000	144000	144000	144000	180000
	A	m ³ /h	72000	72000	108000	108000	108000	108000	144000	144000	180000	180000	216000
	E	m ³ /h	69000	69000	69000	92000	92000	92000	115000	138000	138000	161000	161000
	L	m ³ /h	46000	46000	69000	69000	69000	69000	92000	92000	115000	115000	138000
	N	m ³ /h	92000	92000	92000	115000	115000	115000	138000	161000	161000	184000	184000
	U	m ³ /h	108000	108000	108000	144000	144000	144000	180000	216000	216000	252000	252000
High static pressure	°A,E,L,N,U	Pa	0	0	0	0	0	0	0	0	0	0	0
With static pressure													
Sound power level	°	dB(A)	87,8	87,8	87,8	87,8	90,0	90,0	90,0	92,0	92,5	93,0	94,7
	A	dB(A)	87,8	87,8	90,0	90,0	90,0	90,0	91,5	92,0	93,7	94,2	95,6
	E	dB(A)	84,8	84,8	84,8	86,3	86,3	86,3	87,5	89,0	89,5	90,8	91,3
	L	dB(A)	82,7	82,7	84,8	84,8	84,8	85,6	86,3	87,7	88,5	89,8	90,5
	N	dB(A)	86,3	86,3	86,3	87,5	87,5	87,5	88,5	89,8	90,3	91,5	92,0
	U	dB(A)	90,0	90,0	90,0	91,5	91,5	91,5	92,7	94,2	94,7	96,0	96,5
Without Static pressure													
Sound power level	°	dB(A)	89,7	89,7	89,7	89,7	91,7	91,7	91,7	93,4	93,2	93,5	94,9
	A	dB(A)	89,7	89,7	91,7	91,7	91,7	91,7	93,1	93,4	94,3	94,6	95,8
	E	dB(A)	84,8	84,8	84,8	86,3	86,3	86,3	87,5	89,0	89,5	90,8	91,3
	L	dB(A)	82,7	82,7	84,8	84,8	84,8	85,6	86,3	87,7	88,5	89,8	90,5
	N	dB(A)	86,3	86,3	86,3	87,5	87,5	87,5	88,5	89,8	90,3	91,5	92,0
	U	dB(A)	92,3	92,3	92,3	93,6	93,6	93,6	94,6	95,7	95,5	96,5	96,8
Size													
			0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406
Fans: J													
Fan													
Type	°A,E,L,N,U	type	Axial										
Fan motor	°A,E,L,N,U	type	Inverter										
	°	no.	4	4	4	4	6	6	6	8	8	8	10
Number	A,L	no.	4	4	6	6	6	6	8	8	10	10	12
	E,U	no.	6	6	6	8	8	8	10	12	12	14	14
	N	no.	8	8	8	10	10	10	12	14	14	16	16
Inverter fan													
Air flow rate	°	m ³ /h	64000	64000	64000	64000	96000	96000	96000	128000	128000	128000	160000
	A	m ³ /h	64000	64000	96000	96000	96000	96000	128000	128000	160000	160000	192000
	E	m ³ /h	69000	69000	69000	92000	92000	92000	115000	138000	138000	161000	161000
	L	m ³ /h	46000	46000	69000	69000	69000	69000	92000	92000	115000	115000	138000
	N	m ³ /h	92000	92000	92000	115000	115000	115000	138000	161000	161000	184000	184000
	U	m ³ /h	96000	96000	96000	128000	128000	128000	160000	192000	192000	224000	224000
High static pressure	°	Pa	120	120	120	120	120	120	120	75	75	75	75
	A,U	Pa	120	120	120	120	120	120	120	120	120	120	120
	E,L,N	Pa	200	200	200	200	200	200	200	200	200	200	200
Sound data calculated in cooling mode (1)													
Sound power level	°	dB(A)	87,8	87,8	87,8	87,8	90,0	90,0	90,0	92,0	92,5	93,0	94,7
	A	dB(A)	87,8	87,8	90,0	90,0	90,0	90,0	91,5	92,0	93,7	94,2	95,6
	E	dB(A)	84,8	84,8	84,8	86,3	86,3	86,3	87,5	89,0	89,5	90,8	91,3
	L	dB(A)	82,7	82,7	84,8	84,8	84,8	85,6	86,3	87,7	88,5	89,8	90,5
	N	dB(A)	86,3	86,3	86,3	87,5	87,5	87,5	88,5	89,8	90,3	91,5	92,0
	U	dB(A)	90,0	90,0	90,0	91,5	91,5	91,5	92,7	94,2	94,7	96,0	96,5


(1) Sound power: calculated on the basis of measurements made in accordance with UNI EN ISO 9614-2, as required for Eurovent certification. Sound pressure measured in free field (in compliance with UNI EN ISO 3744).

DIMENSIONS


NRB 0800 - 1100 °
NRB 0800 - 0900 L/A




NRB 1200 - 1600 °
NRB 1000 - 1400 L/A
NRB 0800 - 1000 E/U



NRB 1805 - 2206 °
NRB 1600 - 1805 L/A
NRB 1200 - 1400 E/U
NRB 0800 - 1000 N



NRB 2406 °
NRB 2006 - 2406 L/A
NRB 1600 - 2406 E/U
NRB 1100 - 2406 N



Size			0800	0900	1000	1100	1200	1400	1600	1805	2006	2206	2406
Dimensions and weights without hydronic kit													
A	°	A,E,L,N,U	mm	2450	2450	2450	2450	2450	2450	2450	2450	2450	2450
B	°	A,E,L,N,U	mm	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200
C	°		mm	2780	2780	2780	2780	3970	3970	3970	5160	5160	6350
	A,L		mm	2780	2780	3970	3970	3970	3970	4760	5160	6350	7140
	E,U		mm	3970	3970	3970	4760	4760	4760	5950	7140	7140	8330
N			mm	4760	4760	4760	5950	5950	5950	7140	8330	8330	9520
	Dimensions and weights with pump/s												
	A	°		mm	-	-	-	-	2450	-	-	2450	2450
A,L			mm	-	-	2450	-	-	-	2450	2450	2450	2450
E,U			mm	2450	2450	-	2450	2450	2450	2450	2450	2450	2450
N			mm	2450	2450	2450	2450	2450	2450	2450	2450	2450	2450
B	°		mm	-	-	-	-	2200	-	-	2200	2200	2200
	A,L		mm	-	-	2200	-	-	-	2200	2200	2200	2200
	E,U		mm	2200	2200	-	2200	2200	2200	2200	2200	2200	2200
	N		mm	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200
C	°		mm	-	-	-	-	3970	-	-	5160	5160	6350
	A,L		mm	-	-	3970	-	-	-	4760	5160	6350	7140
	E,U		mm	3970	3970	-	4760	4760	4760	5950	7140	7140	8330
	N		mm	4760	4760	4760	5950	5950	5950	7140	8330	8330	9520
Integrated hydronic kit: 00													
Weights													
Empty weight	°		kg	2390	2430	2500	2540	3030	3080	3110	3810	3980	4020
	A,L		kg	2410	2470	2950	3020	3060	3120	3640	3910	4480	4560
	E,U		kg	2870	2910	2990	3520	3590	3610	4140	4690	4900	5650
	N		kg	3370	3420	3490	3920	3990	4020	4490	5140	5360	6050

Aermec reserves the right to make any modifications deemed necessary.
All data is subject to change without notice. Aermec does not assume responsibility or liability for errors or omissions.

Aermec S.p.A.
Via Roma, 996 - 37040 Bevilacqua (VR) - Italia
Tel. 0442633111 - Telefax 044293577
www.aermec.com